

SMILOG

SOFTWARE FOR MOBILE INTEGRATION IN LOGISTICS

RF TERMINAL CONFIGURATION

TEKTERM V9

Prepared by: M.J. Brandys

Version: 1.5

Dated: October, 2016

Proprietary Information

The recipient of the information in this document hereby acknowledges and agrees that the said information is Proprietary to SMILOG Ltd. and its affiliates and shall not be used, disclosed, and/or duplicated except in accordance with the express written authorization of SMILOG Ltd.

Copyright

© Copyright 2011, SMILOG Ltd.

Trademarks, Registered Trademarks, and Proprietary Names


Product names mentioned in this document may be trademarks or registered trademarks of Psion Teklogix Inc. or other hardware, software, or service providers and are used herein for identification purposes only.

Corporate Address

SMILOG Ltd.
1334 Farrell Ave.
Delta
BC Canada V4L 1V2
Phone: 604-418-5010
Internet: <http://www.smilog.ca>
Email: support@smilog.ca

CONFIGURING TEKTERM V9

After installing TEKTERM from the CAB file, run the program for the first time from
START BUTTON -> Programs -> TekTerm,




This will display the “Launch Menu” Screen.

Note: if TekTerm has been pre-installed it will auto start.
(refer to page 11 if TEKTERM has already been installed)




Double – click on the “Add Session” Button
This will display the “Session Settings” Screen.




Set the following 4 Values:


- 1. “Eumalation (TESS)” via the drop down list
- 2. “Direct TCP” via the drop down list
- 3. IP address or DNS name of TEKRF or TEKCONSOLE server.
- 4. Terminal ID (must be defined on server, and not used by any other terminal)



Press the “Screen...” Button. This will display the “Session Scéen”
Set the Font Rows and Font Columns, (Typically 10 rows x 26 columns or 15 rows x 30 columns)
Then press the “OK” Button




Press the “Advanced” Button
This will display the “Session Advanced” Screen.



Expand the "Characters" Node and set the "Upper Case" to the desired value.


(This will depend on your SAP system. If you required mixed cases passwords, then this should be left at "No". Many TekRf and TekConsole solutions use only Upper Case, requiring that this value be set to "Yes".)



Expand the "Scanner" node, and set **Append F0: = Yes**




Expand the “Fields” node, and set **Field Order: = No**



Expand the “Panning” Node and set **Touch Panning: = No** and **Display Shift: = No**

Then Expand the “Anchor View” Sub-Node and **Set Enabled = Yes**


Note: in earlier versions the X origin and Y origin needed to be set to 0, this is fixed in V9.



Finally, Press the OK button which will return to “Session Settings” Screen.

Press the SAVE button.

Warning: do not press the X at the top of the screen, you will lose all changes.



This will return to the "Launch Menu".

Now press the Global Setting Icon the bottom left of the screen (looks like a gear)



This will display the "Global Settings" Screen.




Expand the "Windows Properties" Node and set **Indicators: = No**
Then press the SAVE button



You will get save / restart message, press Yes

Warning: I have found that sometimes the restart hangs. In this case the only option is a warm restart the terminal: START BUTTON, -> shutdown- > Warm Reset




After a retart you should see the your session. This will appear each time the terminal is restarted.



CONFIGURING TEKTERM AFTER INSTALLATION


Once the system is setup, press CTRL ALT 0 to get to the “Launch Menu”
(press these one at a time, in sequence)



Then press the Icon that looks like a “pad+pen” (red arrow), this will launch the “Session Settings” Screen

If the system is locked in User mode, press Icon that looks like an “lock” (blue arrow), this will display the Security Screen.

Security Screen (PSION TERMINALS ONLY)



Press "Change to Administration mode" button.
A password may be required. The Default password is 123456. If the password has been changed by an administrator it cannot be recovered.




OPTION SETTINGS

1. Change default colors

Expand the "Colour" Node, then expand "Default Colour" Sub-Node.


Set Foreground: = White

Set Background: = Dark Blue



Expand the "Highlight Current Field" Sub-Node.

Set **Enabled: = Yes**



The result will be screen that looks this:




2. Change Sounds.

To enable the sounds found on older Psion Terminals, Go to the Global Settings Screen,
Set **Audio Method : = Beeper**



If you do not want to hear a beep everytime data is entered,
Expand the "Normal" Sub-Node and set **Beep time1: = 0 ms**



Summary of TEKTERM settings on RF devices:

Parameter	Screen Name	
Host Address	Session Settings	<required>
Terminal number	Session Settings	<required >
TESS, Characters: set to upper case Yes	Session Advanced	<optional >
TESS, Scanner: set Append F0 to Yes	Session Advanced	<required>
TESS, Fields: Set Field order to No	Session Advanced	<required>
TESS, Turn off Panning and Set Anchor view to Yes	Session Advanced	<required>
Set Screen Size (rows and columns)	Session Screen	<required>
Turn off indicators (makes more room at the bottom of the screen)	Global Settings	<optional>
Audio: Disable Normal Beep	Global Settings	<optional>